

**Libec**

Craftsmanship from Japan

# LX-ePed

**New**

This patent pending pedestal was specially designed to add the elevating element to a PTZ camera's pan, tilt and zoom features.



# The World's First Electric Pedestal for PTZ Cameras



Electric Elevation Pedestal with Remote Control



Continuous Speed Adjustment



Highly Reliable Wire Connection System



High-Angle Shots



V-mount Battery Powered (optional)



Compatible with Flat-Base Equipment with a 1/4" or a 3/8" Screw Hole



Compatible with Video Heads



Compact Design



User Friendly Accessory Port



Safety Design



Built-in Bubble Level

## LX-ePed **New**

System with floor spreader

<b>Payload</b>	10kg / 22lb
<b>Elevation</b>	400mm / 15.7"
<b>Raising / Lowering speed</b>	Approx. 14 to 40 secs. / movement
<b>Continuous operating time</b>	3 minutes
<b>LAN cable for controller</b>	30m / 98.4'
<b>Power cable</b>	3m / 9.8'
<b>Power</b>	AC100V~240V
<b>Temperature range</b>	-10°C~40°C below RH90%
<b>Battery-powered</b>	Optional
<b>Camera attachment</b>	1/4" and 3/8" screws
<b>Head attachment</b>	100mm / 75mm bowl
<b>Accessory attachment</b>	1/4" and 3/8" screw holes x 2
<b>Bubble level</b>	Available
<b>Weight</b>	11.2kg / 24.6lb
<b>Height</b>	95.3 to 247cm / 37.5" to 97.2"
<b>Section</b>	2-Stage



## LX-ePed Studio **New**

System with dolly

<b>Payload</b>	10kg / 22lb
<b>Elevation</b>	400mm / 15.7"
<b>Raising / Lowering speed</b>	Approx. 14 to 40 secs. / movement
<b>Continuous operating time</b>	3 minutes
<b>LAN cable for controller</b>	30m / 98.4'
<b>Power cable</b>	3m / 9.8'
<b>Power</b>	AC100V~240V
<b>Temperature range</b>	-10°C~40°C below RH90%
<b>Battery-powered</b>	Optional
<b>Camera attachment</b>	1/4" and 3/8" screws
<b>Head attachment</b>	100mm / 75mm bowl
<b>Accessory attachment</b>	1/4" and 3/8" screw holes x 2
<b>Bubble level</b>	Available
<b>Weight</b>	14.2kg / 31.3lb
<b>Height</b>	106.4 to 261cm / 41.8" to 102.7"
<b>Section</b>	2-Stage

