

System	H35 (Head) + QL40B (Tripod) + BR-2B (Mid-level spreader) + FP-1B (Large rubber feet) + RC-50 (Carrying case)		
Payload	8 kg / 17.6 lb	Tilt angle	+90° / -70° (Limited to ±40° with maximum counterbalance)
Weight	5.9 kg / 13.0 lb	Pan angle	360°
Height	① H : 1975 mm W : 780 mm (※Reference)	Counterbalance	Range : 3 ~ 7.5 kg / 6.6 ~ 16.5 lb (C.G. 100 mm)
	② H : 910 mm W : 550 mm (")		Perfect Balance
Folded length	③ L : 944 mm (")		Continuous Counterbalance with Illuminated Meter
Camera plate (Sliding range)	2 Sliding plates (compatible with Manfrotto and Sachtler)	Drag mode	Free plus 3 steps
	One touch attach and release mechanism	Drag system	Multilayered Metal Structure
Plate attachment (Screw sliding range)	Standard : ±30 mm / ±1.2" , Long : ±85 mm / ±3.3"	Temperature range	-40°C ~ +60°C / -40°F ~ +140°F
	Standard : 1/4-20UNC (with video boss)	Head base	Ball 75 mm / Flat base with 3/8" female thread
Spare screw	Long : 1/4-20UNC × 1 , 3/8-16UNC × 2	Carrying handle	Included
	Standard : 68 mm / 2.6" , Long : 85 mm / 3.3"	Section	2-Stage
Bubble level	1/4-20UNC × 1 , 3/8-16UNC × 1	Leg lock system	Flip lock
	Equipped on the top of the head (beneath sliding plate)	Spreader	BR-2B (Telescopic , Removable)
Accessory port	1/4" and 3/8" screw holes (head : 1 set , tripod : 3 sets)	Pan handle	PH-6B (Telescopic)
		Case material	Nylon , Polyester , TPE , PE , PP , POM

Remarks

* Includes adjustment tool.

Exterior Dimensions (mm)

